# **PCB Abatement Plan**

Former Omaha Steel Castings, Co. 4601 Farnam Street

Omaha, Douglas County, Nebraska

March 16, 2016

Terracon Project No. 05147015

### Prepared for:

The Board of Regents of the University of Nebraska (NU) A public body corporate for and on behalf of the University of Nebraska Medical Center 985060 Nebraska Medical Center Omaha, Nebraska 68198-5060

Prepared by:

Terracon Consultants, Inc. Omaha, Nebraska

RECEIVED

AWMD/RCAP

terracon.com



Geotechnical 

Environmental

Facilities

Materials



March 16, 2016

Attn: Omaha, Nebraska 68198-5060 985060 Nebraska Medical Center The Board of Regents of the University of Nebraska (NU)

A public body corporate for and on behalf of the University of Nebraska Medical Center Mr. Keith Swarts

RECEIVED

Re: PCB Abatement Plan Former Omaha Steel Castings, Co. E: kswarts@unmc.edu P: 402-559-5840

AWMD/RCAP

Omaha, Douglas County, Nebraska Terracon Project No. 05147015 4601 Farnam Street

Dear Mr. Swarts:

transformers have concentrations of total PCBs that exceed regulatory screening levels. This reports indicate that two concrete pads at the site formerly used to support electrical addressed in a separate Materials Management Plan. removal and disposal. plan's primary focus is to appropriately address PCB impacted concrete, and to facilitate its Consultants, Inc. (Terracon) for the above referenced site. Previously prepared environmental Enclosed is a Polychlorinated Biphenyl (PCB) Abatement Plan prepared by Terracon Other issues related to upcoming site preparation work are also

concerning this plan or if we may be of further assistance, please contact us at (402) 330-2202. We appreciate the opportunity to be of service to you on this project. If there are any questions

Sincerely,

Terracon Consultants, Inc.

Robert G. Goodwin, PhD., P.G.

for Michael E. Hagemeister, P.E. Senior Principal

**Project Geologist** 

Megan R. Hughes

RGG/MEH/MRH:rgg/kmt

Project Manager

Distribution:

Addressee (1 PDF) Mr. Thomas C. Huston, Cline, Williams, Wright, Johnson & Oldfather LLP (1 PDF) Mr. Kurt Limesand (1 Hard copy)

Terracon Consultants, Inc. P [402] 330 2202 F [402] 330 7606 15080 A Circle Omaha, Nebraska 68144 terracon.com

Environmental Facilities Geotechnical

Materials

### **TABLE OF CONTENTS**

		Page
1.0	INTRODUCTION	1
2.0	PROJECT SCOPE	2
3.0	PROJECT EXECUTION	3
4.0	DOCUMENTATION AND ABATEMENT COMPLETION ACCEPTANCE	4
5.0	NOTIFICATION	4
6.0	HEALTH AND SAFETY	5
7.0	GENERAL COMMENTS	5

### **APPENDIX A – FIGURES**

Figure 1 – Area Map
Figure 2 – PCB Sampling Location Diagram

### APPENDIX B - TABLES

Table 1 – PCB Sampling Results

**APPENDIX C - CERTIFICATION** 

Responsive ■ Resourceful ■ Reliable



### **PCB ABATEMENT PLAN** FORMER OMAHA STEEL CASTINGS, CO. **4601 FARNAM STREET OMAHA, DOUGLAS COUNTY, NEBRASKA**

**Terracon Project No. 05147015** March 16, 2016

### INTRODUCTION

The former Omaha Steel Castings, Co. site (Figure 1, Appendix A) operated as a foundry, and it is slated for redevelopment. Buildings have been demolished and removed from the property, but slabs and foundations remain.

- A Phase I Environmental Site Assessment (ESA) (Terracon Project No. 05137851, April 2, 2014) identified several recognized environmental conditions (RECs) at the site, including:
  - Six concrete pads formerly used to support electrical transformers (Figure 2, Appendix A).
  - Staining was observed on the concrete pads and on soil adjacent to several of the pads.
- A limited sampling investigation (LSI) (Terracon Project No. 05147015, April 7, 2015) was conducted on October 10, 2014, and included wipe sampling of concrete at the six concrete pads and surface soil sampling at three of the pads. Samples were collected from visibly stained areas and were analyzed for polychlorinated biphenyls (PCBs) (Table 1, Appendix B).
- Based on the results of the wipe sampling, concrete core sampling was conducted on March 20, 2015. Three samples each were collected from randomly selected locations at three pads (nine samples total). Concrete was cored to a depth of approximately 7 centimeters (cm) at each location. Samples were analyzed for PCBs (Table 1, Appendix B).

PCB-contaminated concrete from two pads (designated "A" and "F", Figure 2) will be during PCB abatement at the site. Terracon will provide the following services in sup PCB abatement project:

Responsive ■ Resourceful ■ Reliable

port of the			
<b>1</b> 47015R03 rev1.doc			

### PCB Abatement Plan

Former Omaha Steel Castings Co. • Omaha, Nebraska March 16, 2016 • Terracon Project No. 05147015



- disposal of the PCB-contaminated concrete at pads "A" and "F." Coordination of activities with a PCB abatement contractor to conduct removal and
- On-site observation/assistance for removal of concrete impacted by PCBs. Field services contractor on which materials are to be disposed off-site. will consist of observation of the removed materials and Coordinating with the abatement
- Confirmation sampling of sampling of soil beneath the removed pads
- PCB-contaminated concrete from pads "A" and "F." Preparation of a PCB Abatement Report that documents the removal and disposal of the

### NU Contact Information:

Project Coordinator: Keith Swarts, Director, Business Services

402-559-5840

Telephone:

# Abatement Contractor Information

Telephone: Abatement Contractor: John Sempek, Environmental Solutions, Inc.

402-896-3600

# Terracon Contact Information:

Project Manager: Megan Hughes

Telephone: 402-384-7025

# PROJECT SCOPE

cleanup criteria for porous PCB remediation waste for high-occupancy sites is less than or equal concrete, that contain PCBs as a result of spill, release, or other unauthorized disposal. to 1 part per million (ppm). Results of concrete coring (Table 1, Appendix B) indicate that Disposal options for such waste include self-implemented on-site cleanup and disposal. The remediation waste defined in 40 CFR § 761.61 (a) includes porous building materials, such as In accordance with Code of Federal Regulations Title 40 Section 761 (40 CFR § 761), PCB surfaces shall be disposed on-site or off-site as bulk PCB remediation waste. 40 CFR § concentrations less than 50 ppm. In accordance with 40 CFR § 761.61(a)(5)(iii) porous samples collected at pads "A" and "F" exceeded the cleanup criteria, but they have site disposal at a facility permitted, licensed, or registered by a State to manage municipal solid than 50 ppm shall be disposed in accordance with 40 CFR § 761(a)(5)(v)(A) which includes off-761(a)(5)((i)(B)(2)(ii) indicates that bulk PCB remediation waste with a PCB concentration less

Responsive - Resourceful - Reliable

### PCB Abatement Plan

Former Omaha Steel Castings Co. • Omaha, Nebraska March 16, 2016 • Terracon Project No. 05147015



The following scope actions will be implemented to abate site PCB contamination:

- Secure necessary designation and/or manifest from the State or landfill.
- Remove each pad from the ground.
- Break each pad into blocks that can be loaded into dump trucks.
- Secure and tarp removed concrete prior to transport.
- Dispose of the removed concrete and personal protective equipment (PPE) at a landfill licensed to receive municipal waste in accordance with 40 CFR § 761(a)(5)(v)(A).
- Conduct confirmation sampling of soil beneath the removed pads.
- Report the results of removal and disposal.

# 3.0 PROJECT EXECUTION

Pad "A" is approximately 7 feet long by 4 feet 6 inches wide by 2 feet thick. Removal of the concrete pad will result in the removal of about 2.3 cubic yard (cy) of concrete. Pad "F" is approximately 13 feet 7 inches long by 6 feet 1 inch wide by 2 feet thick. Removal of the concrete pad will result in removal of about 6.1 cy of concrete. Access to the site is controlled by locked gates and chain-link fencing. The field work is anticipated to require about two days for concrete removal and disposal. Once on the site property, the concrete pads are readily accessible by vehicles and equipment. The PCB contaminated concrete removal will be conducted, because other pad and foundation removal activities begin. Site restoration will not be remaining concrete pads will follow PCB abatement. The site will be graded to achieve planned surface contours following foundation removal. As such, a detailed execution plan is unnecessary at this time.

The following actions will be implemented:

- Terracon and ESI personnel will coordinate site access with the NU project coordinator.
- A rubber tire backhoe will be used to remove the two concrete pads from the ground.
- A concrete breaker attached to a rubber tire backhoe will be used to break the concrete into pieces able to be loaded into a dump truck.
- A rubber tire backhoe will be used to load the concrete pieces into a dump truck

Responsive Resourceful Reliable



- Concrete chips will be swept up and placed into a dump truck with the concrete pieces.
- Waste will be transported with appropriate manifests to a licensed disposal facility.
- Terracon will conduct confirmation sampling of soil beneath pads "A" and "F" once the pads have been removed. will be sent off site for laboratory analysis of PCBs by Method 8082-SIM. stainless steel bowl (one composite per pad), and two composite samples (one per pad) selected locations per pad. The four individual samples will be composited in a clean Samples of surface soil will be collected from four randomly

## 4.0 **DOCUMENTATION AND ABATEMENT COMPLETION** ACCEPTANCE

methods used to remove PCB-contaminated concrete, waste volumes generated, transportation conducted during the PCB remediation waste abatement process. The report will document the and disposal of waste. Terracon will prepare an Abatement Completion Report this will document the field activities

disposal of the PCB contaminated concrete and confirmation soil sample results less than 1 part per million (ppm). The acceptance criteria for abatement completion will be confirmation of the proper removal and

cleanup area will be discussed. sampling results exceed 1 ppm, Mr. Kurt Limesand, U.S. Environmental Protection Agency Region VII (EPA Region VII) will be contacted (913-551-7184), and possible expansion of the If additional contamination is encountered during the abatement process, or if confirmation

The certification has been signed by the University of Nebraska Medical Center and Terracon. In accordance with 40 CFR § 761.61(a)(3)(E), a written certification is included as Appendix C.

### 5.0 NOTIFICATION

work. Work will commence following EPA Region VII concurrence In accordance with 40 CFR § 761, this work plan will be submitted for review and approval by U.S Environmental Protection Agency Region VII (EPA Region VII) 30 days prior to abatement

Responsive - Resourceful - Reliable

**PCB Abatement Plan**Former Omaha Steel Castings Co. • Omaha, Nebraska March 16, 2016 • Terracon Project No. 05147015




### 6.0 **HEALTH AND SAFETY**


March 19, 2015). PCB Abatement work will be conducted in accordance with Safety and Health Plan, Polychlorinated Biphenyls (PCBs) Contamination Anticipated (Terracon Project No. 05147015,


### 7.0 **GENERAL COMMENTS**

existing site sampling location. stratigraphy, hydrogeology or contaminant distribution which may occur between or beyond sources mentioned in this plan. The data does not account for any variation in subsurface This plan is based on data obtained from previous sampling, analysis and other information

environmental practices within the scope of the client's directives. No warranties are either expressed or implied by this document. This plan has been prepared for the exclusive use of NU for specific application to this project This plan has been prepared in accordance with generally accepted local







- CHRISTMAS TREE SALES LOT
- 3 VACANT BUILDING 708 SOUTH SADDLE CREEK ROAD
- MILITARY SUPPLY STORE 620 SOUTH SADDLE CREEK ROAD
- ACE RENT TO OWN 616 SOUTH SADDLE CREEK ROAD
- STORAGE BUILDING / FORMER DRY CLEANING FACILITY
  600 SOUTH SADDLE CREEK ROAD
- AMERICAN NATIONAL BANK 520 SOUTH SADDLE CREEK ROAD
- 8 VOIGTMAN PROPERTY 609 SOUTH 48th STREET LUST # 021490-99-0007
- METRO HEALTH SERVICE 414 SOUTH SADDLE CREEK ROAD
   UNIVERSITY OF NEBRASKA 412 SOUTH SADDLE CREEK ROAD
- MINUTEMAN CARWASH 404 SOUTH SADDLE CREEK ROAD

- SCHOOL 4469 FARNAM STREET
- TV STATION 4625 FARNAM STREE LUST # APS-2298
- UNIVERSITY OF NEBRASKA MEDICAL CENTER
- QUIK TRIP 715 SOUTH SADDLE CREEK ROAD
- 16 BAKERS GROCERY STORE 4807 LEAVENWORTH STREET
- PARKING LOT
- (18) VACANT LOT

CW-6 CONCRETE SURFACE WIPE SAMPLE

SS-3 SURFACE SOIL SAMPLE

CC-1 •

OMAHA

OMAHA, NE 68144

FAX. (402) 330-7606

CONCRETE CORE SAMPLE
TRANSFORMER CONCRETE PAD

APPROXIMATE SUBJECT SITE BOUNDARY

DRAWING BASED ON AN AERIAL PHOTOGRAPH, GOOGLE EARTH PRO, 2013

REV. DATE BY DESCRIPTION

Consulting Engineers and Scientists

15080 A CIRCLE
PH. (402) 330-2202

FAX. (4

50 100

### PCB SAMPLING LOCATION DIAGRAM

### OMAHA STEEL CASTINGS

4601 FARNAM STREET

	JUB NU.
	ACAD NO
NEBRASKA	FIGURE N

0. 05147015C02 No.: 2

AS SHOWN

4/15/15 05147015

DESIGNED BY: MRH
DRAWN BY: PAI
APPVD. BY: MRH
SCALE: AS S

### Table 1 Omaha Steel Castings Terracon Project No. 05147015

			Analytical Suite			
			Polychlorinated biphenyls, Total PCB-1260	Polychlorinated biphenyls, Total PCB-1260		
			ug/100 cm <sup>2</sup>	mg/kg (ppm)		
Transformer		Sample				
Designation	Sampling Location	Type				
Δ.	CW-1	Wipe	4.98	N/A		
Α	CCS-1, CCS-2, CCS-3	Core	N/A	1.20	1.18	1.20
В	CW-2	Wipe	<1.00	N/A		
В	SS-1	Soil	N/A	<0.0495		
С	CW-3	Wipe	<1.00	N/A		
D	CW-4	Wipe	<1.00	N/A		
	CW-5	Wipe	10.2	N/A		
E	CCS-4, CCS-5, CCS-6	Core	N/A	0.254	0.186	0.207
	SS-2	Soil	N/A		0.159	
	CW-6	Wipe	2.64		N/A	
F	CCS-7, CCS-8, CCS-9	Core	N/A	1.48	0.603	0.318
	SS-3	Soil	N/A		0.231	

< = less than

ppm = parts per million

mg/kg = miligram per kilogram

ug/100cm<sup>2</sup> = micrograms per 100 square centimeters

N/A = not applicable

### **Notes**

- 1) The samples were submitted for laboratory analysis of PCBs by EPA Method 8082; sample results for PCB-1016, PCB-1221, PCB-1232, PCB-1242, PCB-1248, PCB-1254, and PCB-1268 were reported as non-detect and are not listed on the table above.
- 2) Surface soil samples (SS-1 through SS-3) were collected on October 10, 2014. Samples were collected near concrete pads at locations where soil staining indicated the potential for PCBs to have released from the concrete pad onto the ground surface.
- 3) Concrete wipe samples (CW-1 through CW-6) were collected on October 10, 2014. A 100 cm<sup>2</sup> template was used to collect the sample from the sample area.
- 4) Concrete core samples (CCS-1 through CCS-9) were collected on March 20, 2015. Samples were collected from three random locations on each transformer pad.
- 5) For locations where a duplicate sample was collected, the higher concentration is recorded.

Keith Swarts Omaha, Nebraska, and are available for EPA Inspection. instrumental/chemical analysis procedures used to characterize the PCB contamination at the University of Nebraska cleanup site, are on file at the UNMC Environmental Office located at 4230 Leavenworth Street, sample collection procedures, sample preparation procedures, extraction procedures, and In accordance with 40 CFR § 761.61(a)(3)(E), the undersigned certify that sampling plans, PCB Abatement Plan
Former Omaha Steel Castings Co. • Omaha, Nebraska
March 16, 2016 • Terracon Project No. 05147015 Medical Center CERTIFICATION Delonal Manne My P. Higher Terracon Consultants, Inc. Megan R. Hughes

Interim Vice Chancellor
for Business & Finance
University of Nebraska Medical Center
on behalf of Keith Swarts

Responsive - Resourceful - Reliable

6 05147015R03 rev1 doc

lectacon